



COIL SPRING COBRAS

427 SPECIFICATIONS



PRICE	
List price.....	\$6995
ENGINE	
Number of cylinders & type.....	V-8, OHV
Bore & Stroke, In.	4.24 x 3.87
Displacement, cubic-inches.....	427
Compression ratio.....	10.4:1
BPH @ RPM.....	425 @ 6000
Torque @ RPM, lb-ft, est.....	480 @ 3500
Carburetors, make & size (CFM).....	2 Holley 600
DRIVE TRAIN	
Clutch dia, In.	11.5
Transmission.....	Ford Top-Loader
Gear ratios: 1st.....	2.32
2nd.....	1.69
3rd.....	1.29
4th.....	1.00
Differential Type.....	Salisbury Limited Slip
Ratio.....	3.54:1
CHASSIS & SUSPENSION	
Frame type.....	Ladder-type steel tube
Brake type, F/R.....	disc/disc
Front brake dia,	11.63
Rear brake drum dia x width, In.	10 x 7.5
Steering type.....	recirculating ball
Overall ratio.....	19:1
Turns, lock to lock.....	2.50
Turning circle, ft.....	36
Front suspension.....	Independent with A-arm, coil springs, tube shock absorbers
Rear suspension.....	Independent with A-arm, coil springs, tube shock absorbers
Wheel size, dia. x width, In.	15 x 7.5
Tire make and model.....	Goodyear Blue Dot
Size.....	8.15x15
MISCELLANEOUS	
Body style available.....	2-door roadster
Seating capacity, persons.....	2
Fuel tank capacity, gals.	18
Crankcase capacity, qts.	9

OPTIONS

Hard Top
Roll Bar
Hood Scoop
Oil Cooler
Available colors: Red, Maroon, White, Charcoal, Guardsman
Blue, Silver, Ivy Green
Available interior color: Black

GENERAL

Curb weight, lbs. 2354
Test weight, lbs. 2529
Weight distribution, F/R, %..... 48/52
Wheelbase, In. 90
Track, F/R, In. 56/56
Overall length, In. 156
Overall width, In. 68
Overall height, In. 49

PERFORMANCE*

Acceleration: 0-30 MPH, sec. 3.3
0-40 MPH..... 3.6
0-50 MPH..... 3.9
0-60 MPH..... 4.3
0-70 MPH..... 5.5
0-80 MPH..... 6.2
0-100 MPH..... 8.8
Quarter mile, seconds @ MPH..... 12.22 @ 118
Top speeds, MPH: 1st gear (7000 RPM)..... 69
2nd gear (7000 RPM)..... 95
3rd gear (7000 RPM)..... 124
4th gear (6900 RPM)..... 160

*Performance data extrapolated from period road tests in national magazines

